



GB04/3806



PRIORITY DOCUMENT

SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ 21 OCT 2004

WIPO	PCT
------	-----

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

I also certify that the application is now proceeding in the name as identified herein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

Dated 1 October 2004

BEST AVAILABLE COPY




INVESTOR IN PEOPLE

GB0326402.5

By virtue of a direction given under Section 30 of the Patents Act 1977, the application is
proceeding in the name of:-

PITCHLINE LIMITED
Incorporated in the United Kingdom
24a Francis Street
Lurgan
Armagh
BT66 6DN
United Kingdom
ADP No. 08883118001

Patents Form 1/77

Patents Act 1977
(Rule 16)13NOV03 E85166391 D02884
P01/7700 0.00-0326402.5**Request for grant of a patent**

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road
Newport
South Wales
NP10 8QQ

1. Your reference

P35990/CAM/MEA

2. Patent application number

(The Patent Office will fill in this part)

0326402.5

3. Full name, address and postcode of the or of each applicant (underline all surnames)

Barry Douglas
24a Francis Street
Lurgan, ACT APPLICATION FILE NUMBER 28/5/04
Armagh BT66 6DN

Patents ADP number (if you know it)

8752404001

If the applicant is a corporate body, give the country/state of its incorporation

United Kingdom

4. Title of the invention

"Method of Marking Pitch Lines"

5. Name of your agent (if you have one)

Murgitroyd & Company

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

Scotland House
165-169 Scotland Street
Glasgow
G5 8PL

Patents ADP number (if you know it)

1198015

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number (if you know it)

Date of filing (day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing (day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if
a) any applicant named in part 3 is not an inventor, or
b) there is an inventor who is not named as an applicant, or
c) any named applicant is a corporate body.
See rule (d))

No

Patents Form 1/77.

9. Enter the number of sheets for any of the following items you are filing with this form.
Do not count copies of the same document

Continuation sheets of this form

Description 9

Claim(s) -

Abstract -

Drawing(s) 2

D
only
D

10. If you are also filing any of the following, state how many against each item.

Priority documents -

Translations of priority documents -

Statement of inventorship and right to grant of a patent (Patents Form 7/77) -

Request for preliminary examination and search (Patents Form 9/77) -

Request for substantive examination (Patents Form 10/77) -

Any other documents (please specify) -

11.

I/We request the grant of a patent on the basis of this application.

Signature Murgitroyd & Company

Date 13 November 2003

12. Name and daytime telephone number of person to contact in the United Kingdom

Mark Eamshaw

02890 320441

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

1 Method of Making Pitch Lines

2

3 The present invention relates to a method of making
4 lines in ground suitable for playing fields and the
5 like.

6

7 In the island of Ireland, there are approximately
8 120,000 playing pitches for soccer, gaelic football,
9 cricket and the like. The lines for such pitches are
10 generally formed by a wheeled paint buggy, which
11 introduces a line of paint on the ground through the
12 travel of the front wheel through a paint reservoir.

13

14 However, heavily used pitches often require newly
15 painted lines every week during a playing season,
16 whereas these lines are often 'lost' in the non-
17 playing season as the surrounding grass encroaches,
18 and the pitches are not so regularly mowed. Weed or
19 grass killer can be added to the intended line, but
20 because grass is on either side of each line, the
21 grass and weeds still encroach quickly. It will be
22 appreciated the amount of time taken by groundsmen

1 to keep clearing and repainting pitch lines for
2 120,000 pitches in Ireland alone.

3

4 It is an object of the present invention to provide
5 more permanent lines in the ground.

6

7 Thus, according to one aspect of the present
8 invention, there is provided a method of creating a
9 marked line in a ground surface comprising the steps
10 of:

11 forming one or more slits in the ground surface;
12 inserting a line of material in the or each slit
13 such that part of the material is visible above the
14 ground surface.

15

16 The slit in the ground surface could be formed by
17 any suitable means, one such being a blade,
18 preferably having a sharpened or tapered edge to
19 assist entry into and through the ground surface.

20

21 The ground surface can be any surface on which a
22 slit can easily be formed, one such being earth,
23 more generally grassed earth.

24

25 In one embodiment of the present invention, the
26 method comprises forming between two and four slits,
27 preferably three slits, parallel in the ground, so
28 as to create a broader form of marked line. Where
29 the method involves forming multiple lines, the
30 lines can be any suitable distance apart. Where it
31 is intended generally to provide a single visible
32 marked line in the ground surface, the multiple

1 slits are preferably relatively close, such as 20mm,
2 inter-distant.

3

4 The or each slit created preferably creates little
5 or no visible disturbance on the ground surface
6 other than the marked line. Preferably, the ground
7 surface is rolled after the insertion of the or each
8 line of material.

9

10 The material may be any suitable material, at least
11 part of which is visible above the ground surface.
12 The material may be any suitable colour, white being
13 the commonest colour for many playing pitches.

14

15 Preferably, at least that part of the material
16 visible above the ground surface is partially or at
17 least substantially resistant to sunlight, in
18 particular UV light. In this regard, the material
19 may inherently have a high kilo-langley strength, or
20 be treated so as to have such a high strength.

21

22 In another embodiment of the present invention, the
23 material is at least partly open or has an open
24 structure, through which the ground surface, or
25 anything growing in the ground surface, such as the
26 roots of grass, etc, can extend so as to help anchor
27 the material in the slit either immediately and/or
28 over time.

29

30 According to another embodiment of the present
31 invention, the material is a polymer material such

1 as polypropylene. Such material is widely
2 available.

3
4 The material is preferably inserted in the slit by
5 travel on the slit-forming means. More preferably,
6 the material travels on the edge of the slit-forming
7 means towards and into the surface, and is located
8 in the slit as the slit is being formed.

9
10 More preferably, at least a portion of the material
11 which is not inserted into the ground surface
12 comprises a number of separate or discrete fibres,
13 or fibre-like extensions. These together provide
14 the visual form of the line, but are wholly or
15 substantially individual like blades of grass. More
16 preferably, that portion of the material above the
17 ground surface is not damageable by a lawnmower or
18 ground trimmer or the like.

19
20 According to one embodiment of the present
21 invention, the material comprises a woven plastics
22 material, having a central woven portion which is
23 insertable in the ground surface, and extended weft
24 fibres adapted to partially or substantially
25 extended above the ground surface.

26
27 Thus, according to one embodiment of the present
28 invention, there is provided a method of creating a
29 marked line in a ground surface comprising the steps
30 of:

1 locating a slit-forming means having at least one
2 blade on the ground surface, such that a portion of
3 the blade enters the ground surface;
4 locating a fibrous or woven material on each blade;
5 traversing the slit forming means along the path of
6 the intended line;
7 allowing the material to travel with each blade into
8 the ground;
9 leaving the material in each slit formed such that
10 part of the material is visible above the ground
11 surface.

12
13 According to a further embodiment of the present
14 invention, the marked line formed by the present
15 invention is 'permanent', i.e. remains to form a
16 marked line for at least a number of years,
17 expectantly greater than ten years.

18
19 In a second aspect, the present invention extends to
20 a marked line in the ground surface formed by the
21 method as hereinbefore described.

22
23 According to a third aspect of the present
24 invention, there is provided a marked line forming
25 apparatus, which apparatus comprises one or more
26 rotatable blades, each blade being adapted to form a
27 slit in the ground surface, and adapted to feed
28 around its edge a material for partially inserting
29 into the slit.

30
31 Preferably the apparatus includes a roller following
32 the or each blade, more preferably two or more

1 rollers on which the apparatus traverses along the
2 ground surface.

3
4 Embodiments of the present invention will now be
5 described by way of example only, and with reference
6 to the accompanying drawings in which:

7
8 Figure 1 is a marked line in a grassy earth surface
9 according to one embodiment of the present
10 invention;

11 Figures 2 a and b are diagrammatic cross sections of
12 the ground in Figure 1 from different directions;
13 Figure 3 is a perspective part view of apparatus
14 according to another embodiment of the present
15 invention;

16 Figure 4 is a schematic part-cross sectional side
17 view of part of the apparatus in Figure 3 in use.

18
19 Referring to the drawings, Figure 1 shows a marked
20 line 2 in a grassy earth-surface 4 as an
21 illustration of the effect of the present invention.
22 The marked line could be used as a pitch line for a
23 soccer or gaelic football pitch.

24
25 Figure 2a shows a cross sectional view through the
26 ground 4 across the path of the marked line 2,
27 showing the location of three lines 6 of white
28 material in the ground surface 4. Figurative grass
29 8 is shown each side of the line 2, although the
30 relative heights of the grass 8 and the parts of the
31 material above the ground surface are for
32 illustrative purposes only.

1

2 It is possible that the grass 8 will re-grow around
3 the visible part of the material. However, material
4 such as polypropylene is not cuttable by most if not
5 all types of lawnmowers, especially those lawnmowers
6 used generally to mow playing surfaces. Thus, it is
7 not a problem if the grass grows in amongst the
8 marked white lines 6, as mowing of the playing
9 surface will reduce it to the same or a lower height
10 of the visible polypropylene fibres, maintaining the
11 visibility of the white lines 6.

12

13 Figure 2b shows a longitudinal cross section of the
14 marked line 2 of Figure 1, showing the material
15 having a woven section 10 which is within the ground
16 surface 4, and the free fibres extending therefrom,
17 the ends of which 12 are visible above the ground
18 surface.

19

20 That part of the material above the ground surface 4
21 is labelled in Figures 2a and 2b as 20, and that
22 part which is below the ground surface 4 is labelled
23 22. The combined parts of the material 20, 22 can
24 be seen as folded, which folding is arranged to fit
25 over the edge of a blade as hereinafter described.

26

27 Figure 3 shows apparatus comprising three blades 30.
28 The blades are rotatable about separate axes 32,
29 parallel, and are offset to be approximately 20mm
30 apart, which distance is adjustable.

31

1 Figure 4 shows schematically the three blades 30,
2 generally housed within a housing 34. At the
3 forward and rear ends of the housing 34 are round
4 surface rollers 36.

5
6 Each blade 30 forms a slit in the ground surface 4
7 by traversing the ground surface 4, eg by being
8 pulled by a tractor through linkage 38. As each
9 blade 30 rotates about its axis 32, it cuts into the
10 ground surface 4.

11
12 Feeding onto each blade 30 (shown only once in
13 Figure 4), is a folded woven polypropylene material
14 approximately 20cm wide, having a central woven band
15 approximately 7-8cm wide, and free weft fibres
16 extending from each side of the central band. The
17 fully woven form of this material is common in the
18 art, and used for forming bales or agricultural
19 flexible sacks and the like.

20
21 As the blades 30 rotate, the folded material 40
22 follows the edge of the blade 30 and is therefore
23 fed into the ground surface 4 as the blade 30 enters
24 also. The force of the blade 30 then locates the
25 base of the material 40 in the slit formed, which
26 material 40 then remains in the ground surface 4
27 whilst the edge of the blade 30 exits the ground
28 surface 4. The free ends 42 of the material 40 are
29 however now visible whilst being securely retained
30 in the ground surface 4 as the ground folds back
31 around the remaining part of the material and holds
32 it in place.

1
2 Any ground disturbance caused by the slits is rolled
3 by the rear roller 36.

4
5 In order to ensure straight lines, the apparatus-
6 pulling means such as the tractor, could be laser
7 guided by a laser set at the end of the intended
8 path of the line, whose beam hits a target on or
9 near the apparatus, which target is noted by the
10 user.

11
12 The present invention has been found to lay the
13 complete lines of the football pitch within a day,
14 which lines then need no further maintenance or
15 repair. Moreover, the free fibres 20 extending
16 above the ground surface will not trip or catch any
17 player, such as by his boots studs. Moreover, the
18 free fibres 20 cannot be cut by a lawnmower such
19 that mowing any playing pitch is not a problem.

20
21 The present invention provides a simple but
22 effective means of providing marked lines, which
23 lines will remain, and need no further repair or
24 maintenance for a number of years, while still
25 providing the same visual effect as painted lines.

13-11-03

12:12

From-Murgitroyd & Co.

02890320442

T-885 P1013/014 F-864

1/2

Fig 3





Fig 1



2/2






Fig 4



**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record.**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- BLACK BORDERS**
- IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- FADED TEXT OR DRAWING**
- BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- SKEWED/SLANTED IMAGES**
- COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- GRAY SCALE DOCUMENTS**
- LINES OR MARKS ON ORIGINAL DOCUMENT**
- REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.